

unbalanced

IY204

Unbalanced Stereo Patch Cable - IY204

- extremely flexible
- compact construction (4.0 mm x 8.0 mm)



Patch / Studio / Outdoor

Conductor	stranded bare copper, 7 x 0,20 mm
Cross Section	0.22 mm ²
Core Insulation	PE
Single Core Shielding	bare copper spiral shield
No. of Cores	2
Core Arrangement	parallel, separable
Outer Jacket	PVC, matt
Dimensions	4,0 x 8,0 mm

Leiteraufbau	blanke Cu-Litze, 7 x 0,20 mm
Leiterquerschnitt	0.22 mm ²
Aderisolation	PE
Einzeladerabschirmung	blanker Cu-Wendelschirm
Aderanzahl	2
Aderanordnung	parallel, aufreißbar
Außenmantel	PVC, matt
Abmessungen	4,0 x 8,0 mm

Min. Bending Radius	20 mm
Working Temperature	-20 °C / +70 °C

Min. Biegeradius	20 mm
Betriebstemperatur	-20 °C / +70 °C

Conductor Resistance	< 85 Ω/km
Capacitance	130 pF/m
Insulation Resistance	> 1 GΩ x km

Leiterwiderstand	< 85 Ω/km
Kapazität	130 pF/m
Isolationswiderstand	> 1 GΩ x km

■ black

Order Code Bestell-Nr.	Colour Farbe	Weight Gewicht	Standard Length [m] Standard Längen [m]	Max. Length / Reel Max. Länge / Spule
IY204	black	40 g/m	100 / 500	1000 m