

balanced


Microphone

**MC2000..**


**Professional Microphone Cables - MC2000..**

- very low capacitance (60 pF/m)
- extremely flexible
- extra heavy overall sheath




 <b>Conductor</b>	<b>stranded bare copper, 28 x 0,10 mm</b>
<b>Cross Section</b>	<b>0.22 mm<sup>2</sup></b>
<b>Insulation</b>	<b>PE</b>
<b>Core Arrangement</b>	<b>2 cores + cotton tracers twisted</b>
<b>Shielding</b>	<b>bare copper spiral shield</b>
<b>Outer Jacket</b>	<b>PVC, matt</b>
<b>Overall Diameter</b>	<b>6,5 mm</b>

Leiteraufbau	blanke Cu-Litze, 28 x 0,10 mm
Leiterquerschnitt	0.22 mm <sup>2</sup>
Isolation	PE
Aderanordnung	2 Adern + Baumwollfäden verseilt
Abschirmung	blanker Cu-Wendelschirm
Außenmantel	PVC, matt
Außendurchmesser	6,5 mm

 <b>Min. Bending Radius</b>	<b>30 mm</b>
<b>Working Temperature</b>	<b>-20 °C / +70 °C</b>

Min. Biegeradius	30 mm
Betriebstemperatur	-20 °C / +70 °C

 <b>Conductor Resistance</b>	<b>&lt; 85 Ω/km</b>
<b>Capacitance</b>	
<b>Cond./Cond.</b>	<b>60 pF/m</b>
<b>Cond./Shield</b>	<b>110 pF/m</b>
<b>Insulation Resistance</b>	<b>&gt; 100 MΩ x km</b>

Leiterwiderstand	< 85 Ω/km
Kapazität	
Ader/Ader	60 pF/m
Ader/Schirm	110 pF/m
Isolationswiderstand	> 100 MΩ x km

■ SW [black]    ■ BL [blue]    ■ RT [red]

Order Code Bestell-Nr.	Colour Farbe	Weight Gewicht	Standard Length [m] Standard Längen [m]	Max. Length / Reel Max. Länge / Spule
MC2000SW	black	50 g/m	100 / 500	2500 m
MC2000BL	blue	50 g/m	100 / 500	2500 m
MC2000RT	red	50 g/m	100 / 500	2500 m