

VERSATAP 30/50

VERSATAP 30 4" 2-Way Speaker with Transformer

Built-in 70.7 V transformer with 4 tap positions (2, 4, 8, 16 W) and 8 ohms bypass
Compact and lightweight
Housing is strong, rigid and weather resistant

VERSATAP 50 6 1/2" Molded Speaker with Transformer

Built-in 70.7 V transformer with 4 tap positions (2.5, 5, 10, 20 W) and 8 ohms bypass
Compact and lightweight
Housing is strong, rigid and weather resistant



VERSATAP 30 FEATURES

- ▶ Power capacity: 30W (8 Ω)
- ▶ Sensitivity: 84 dB SPL @ 1W / 1M
- ▶ Frequency response: 120Hz ~ 20kHz / 75Hz ~ 20kHz
- ▶ 4" poly carbon woofer and 1" soft dome
- ▶ Built-in 70.7 V transformer with 4 tap positions (2, 4, 8, 16W) and 8 Ω bypass
- ▶ Compact and lightweight
- ▶ Moisture resistant
- ▶ Aluminum enclosure, available in both black and white
- ▶ U-mount bracket included

VERSATAP 50 FEATURES

- ▶ Power capacity: 50W (8 Ω)
- ▶ Sensitivity: 90 dB SPL @ 1W / 1M
- ▶ Frequency response: 120Hz ~ 20kHz / 75Hz ~ 20kHz
- ▶ 6.5" poly carbon woofer and 1" soft dome
- ▶ Built-in 70.7 V transformer with four tap positions (2.5, 5, 10, 20W) and 8 Ω bypass
- ▶ Compact and lightweight
- ▶ Moisture resistant
- ▶ Aluminum enclosure, available in both black and white
- ▶ U-mount bracket included

Versatap Series are contractor-friendly speakers. Each speaker is fitted with a 100V (70.7V available) Line transformer, 4 power rating tap positions and an 8 ohms bypass position to allow for almost universal application in any PA system. The cabinet of the Versatap 30 is lightweight and of aluminum construction. It provides a strong, rigid housing, weather resistant capability, and is available in black or white.

Versatap Series are contractor-friendly speakers. Each speaker is fitted with a 100V (70.7V available) Line transformer, 4 power rating tap positions and an 8 ohms bypass position to allow for almost universal application in any PA system. Both the Versatap 30 and Versatap 50 are supplied with a U-mount bracket. The Versatap 50 can also be used with the (optional) RK15 Universal Swivel Mount, which allows for 270 degree aiming of the speaker for ease of positioning and sound.

PHONIC

VERSATAP 30/50

Specifications

Versatap30	
Maximum Power Rating	30 watts(8 ohms)
Frequency Response	120Hz~20KHz
Sensitivity@ 1W/1M, 1KHz	84dB
Woof Size	4" Polycarbon
Tweeter Size	1" Soft dome
70.7 Tap Positions	2, 4, 8, 16W
Dimensions(HxWxD)	184.2x114.3x108 mm (7.25"x4.5"x4.25")

Versatap50	
Maximum Power Rating	50 watts(8 ohms)
Frequency Response	75Hz~20KHz
Sensitivity@ 1W/1M, 1KHz	90dB
Woof Size	6.5" Polycarbon
Tweeter Size	1" Soft dome
70.7 Tap Positions	2.5, 5, 10, 20W
Dimensions(HxWxD)	292x197x210 mm (11.5"x7.75"x8.25")



Back Panel



V1.1
1/03/05
Information in this document is
subject to change without notice.

PHONIC