

PHONIC VERSATAP SERIES

VERSATAP 30 AND VERSATAP 50

THANK YOU FOR PURCHASING THE **PHONIC VERSATAP SERIES** OF SPEAKERS. THESE COMPACT, WEATHER-RESISTANT SPEAKERS ARE DESIGNED FOR CLEAR, ARTICULATE SOUND REPRODUCTION IN MANY DIFFERENT APPLICATIONS. FOR YOUR CONVENIENCE, **VERSATAP** SPEAKERS ARE AVAILABLE IN BOTH BLACK AND WHITE COLORS. EACH SPEAKER IS EQUIPPED WITH A 100V TRANSFORMER WITH 4 TAP POSITIONS, AND AN 8 OHM BYPASS POSITION. 100V AND 8 OHM OPERATION ARE NOT INTERCHANGEABLE, AND DOING SO WILL DAMAGE THE SPEAKER, AMPLIFIER, OR BOTH UNITS. PLEASE VERIFY WHICH YOU WILL BE USING BEFORE APPLYING SIGNAL TO THE SPEAKER.

CAUTION: THIS IS NOT A WATERPROOF UNIT, SO EXPOSURE TO WATER MAY CAUSE DAMAGE TO THE SPEAKER AND/OR ELECTRICAL SHOCK. PLEASE OBSERVE THE MAXIMUM ALLOWABLE POWER RATING TO PREVENT OVERLOADING AND DAMAGE THE SPEAKER.

WHEN INSTALLING THE **VERSATAP** SPEAKERS, PLEASE POSITION THEM IN A MANNER THAT REDUCES EXPOSURE TO THE ELEMENTS (WATER, SNOW, SUN, ETC.). THIS WILL INCREASE THE LIFE OF THE SPEAKERS AND PROTECT THE SPEAKER CONES FROM DAMAGE. **VERSATAP** SPEAKERS SHOULD BE POINTING DOWNWARDS OR HORIZONTALLY TO PREVENT ACCUMULATION OF WATER IN THE SPEAKER.

IT IS RECOMMENDED THAT YOU MOUNT THE U-MOUNT OR RK-15 UNIVERSAL SWIVEL MOUNT BRACKETS TO THE DESIRED LOCATION FIRST BEFORE ATTACHING THE SPEAKER. THIS WILL ALLOW THE SPEAKER TO BE AIMED PROPERLY. PLEASE DO NOT OVERTIGHTEN THE SPEAKER MOUNTING KNOBS. AS THIS WILL DAMAGE THE MOUNTING THREADS.

	VERSATAP 30	VERSATAP 50
MAXIMUM POWER RATING	30 WATTS (8 OHM)	50 WATTS (8 OHM)
FREQUENCY RESPONSE	120HZ-20KHZ (± 3 DB)	75HZ-20KHZ (± 3 DB)
SENSITIVITY	84dB	90dB
WOOFER SIZE	4" POLYCARBON	6.5" POLYCARBON
TWEETER SIZE	1" SOFT DOME	1" SOFT DOME
100 TAP POSITIONS	2,4,8, 16W	2.5,5,10,20W
VC DIRECT	8 OHMS	8 OHMS
DIMENSION	7-1/4"X4-1/2"X4-1/4"	11-1/2"X7-3/4"X8-1/4"

PHONIC